

APPENDIX A Revision A	TRAILER MOUNTED SUPPORT SYSTEM PRODUCT DATA SHEET		
Company	DHS Systems LLC		
Part Number or NSN	TG201-0008G DRASH HP-2C/188, OD Green, Analog		
Specifications as applicable			
Safety and Mobility Certification by Military Test Center			
Trailer			
Stowage Components included with trailer	NA		
Cargo Volume Stowage, For shelter and accessory components In cubic feet	77 cu. ft.		
Physical Dimensions for trailer	6.5 ft H		
Height	7.2 ft W		
Width	16.2 ft L		
Length Recommended Prime Mover Vehicle			
Recommended Prime Mover vehicle	нмми∨	Requires a vehicle capable of towing a 4,200 lb. trailer.	
Empty GVW	3,549 lb.		
Tongue Weight	379 lb.		
Tire Type and Size	Radial	Two 37 x 12.50 x 16.5 LT Goodyear Wrangler R/T II, Load Rating C bias-ply, run-flat tires.	
Fuel Tank Capacity	16 gal.		
Generator			
Nominal Output in kW, Volts AC, Hertz, Phase	18kW	120/208 Volt, 3-Phase, 60 Hz	
Operating Environment	All	Operating Range from -50 °F to +140 °F.	
Engine type	Diesel	Four cylinder, liquid cooled, direct injection, 1800 RPM.	
Fuel Type	Diesel	Can also use JP8 or JP5.	

E 10 "		
Fuel Consumption		
(AC Compressor On)	1.10	
At 25% load	NA	
At 50% Load	NA	
At 75% Load	NA	
at maximum output	1.25	
Noise in DB at 25 feet	İ	
(AC Compressor On)		
At 25% load	NA	
At 50% load	NA	
At 75% Load	NA	
At maximum rated load	76 dB	
Heater	1	
Nominal Output in BTU's	NA	
Electric Requirement Volts/Amps	NA	
Air Conditioning		
Maximum Cooling Capacityin	1	
BTU's		96,000 BTU/hr
Maximum Heat Output		2 stage heat 92,000 BTU/hr electric heat. 80,000 BTU/hr fuel fired A
Capacity in BTU's		2 dags float 62,000 B 1 9/11 discalls float. 60,000 B 1 9/11 floor file a 7
Refrigerant Type	D 407 0	
	R407-C	
CFM Air Flow		
	3,000 CFM	ĺ
Air Duct Diameter		
All Buck Blainleter	4 Ducts	Two 14 in Supply Two 14 in Return
	1 Duoto	The first apply the first count
Power Requirements in kW, VAC, HZ,		
Phase		
	28kW	208 VAC, 60 Hz, 3-phase.
		, , ,
10. 1.1/4.1.11/4		
Special/Additional Features:	The UD OC	/100 Trailer provides three primary factures for the and year of a
		/188 Trailer provides three primary features for the end user of a
		ASH shelter: cargo space, environmental control and electrical power.
		cubic foot cargo area, includes a 16-gallon fuel tank and comes with
	an 18kW G	enset and an 8-ton ECU.
	INCLUDES:	
	Drip Berm (P/N: T295188), qty. = 1	
	Trailer Electrical Set (P/N: T2-95220), qty. = 1	
	Trailer Push Package (P/N: TR20IS), qty. = 1	
	Auxiliary Fuel Kit (P/N: TG430-6001-PH), qty. = 1	
	Air Supply Duct (P/N: T291230), qty. = 2	
	Air Return Duct (P/N: T291432), qty. = 2	
	Fire Extinguisher, 5lbs, (P/N T295175), Qty. = 1	